



Complete Solutions For LED Screens - RENTAL & SALE

info@digitalscreenindia.com  
www.adigitalscreenindia.com

## 5mm Technical Specification

Model No.	LIPL-P5-1R1G1B(3in1)
Dimension (WxH)	160mm x 80mm
Cabinet Size	640 X 640
Module Resolution	32 x 16
Density (pixels/m <sup>2</sup> )	40000
Brightness Density	1800 cd/m <sup>2</sup>
Viewing distance	3m ~100m
Power consumption (Avg)	600 w/m <sup>2</sup>
Power consumption (Max)	1400 w/m <sup>2</sup>
Weight	35 kg/m <sup>2</sup>
Drive Mode	1/8 scanning
Viewing angle	Horizontal angle: 120°; Elevation angle: 60°; Depression angle: 60°
Gray scale	256 gray scale in each red, green, blue color
Colors	16 Million Colors
Refresh Velocity	= 60 frame/sec
Refresh Rate	Up to 4800HZ
Display Life	> 100 k hours
Display MTBF	10,000 hours
Blind Pixels Rate	= 0.0003
Working Voltage	AC 230V±15% 47 ~ 64HZ
Effective Control Distance	100m (1000 BASE-T Ethernet cable) 500 mtrs (optical fiber)
Operation Temperature	-20° C ~ 60° C
Operation Humidity	10% ~ 90%RH

C-202, Orion Vasant Galaxy, Link Road, Goregaon (W), Mumbai 400 090

267/2124, Road No-7, Motilal Nagar-1, Near Vibgyor School, Goregaon (W), Mumbai 400 104, Tel: (022) 28766246 | 22928774

MUMBAI | Pune | Gujarat | New Delhi | UP